

The business for business

The elegantly slim 17" ViewSonic VG721m LCD monitor combines multimedia versatility with a new design. Thanks to the ClearMotiv™ 8ms video response time, images appear with pinpoint focus and superior clarity when viewing moving images. Premium contrast ratio and brightness levels ensure superb picture quality that astonish with their vivid, brilliant colours. The integrated 3-watt speakers enrich your desktop with rich stereo sound and let you enjoy a true multimedia experience. The fully-featured VG721m is an ideal LCD monitor for home, small/home office, corporate, government or education use.

VG721m

**17" LCD MONITOR
WITH CLEARMOTIV™
8MS VIDEO RESPONSE**

It's not just a multimedia LCD. It's a ViewSonic.



8MS RESPONSE FOR MULTIMEDIA EXCELLENCE

- > **ClearMotiv™ 8ms video response time**
Ultra-fast 8ms video response delivers broadcast-quality full motion video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **Multimedia enhanced**
Save workspace and enjoy rich stereo sound with built-in stereo speakers.
- > **Ultra-high 600:1 contrast ratio (typ.) and 280cd/m² brightness (typ.) and for rich, detailed images**
- > **OnView® controls for superior screen adjustability**
Screen adjustments are precisely made via an easy-to-use on-screen menu.
- > **VESA 100mm wall mount interface and Kensington® security port**
- > **1280 x 1024 resolution**
- > **PC and Mac® compatible**
- > **TCO'03 and ENERGY STAR® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic® 
the choice of professionals

VG721m

17" LCD MONITOR WITH CLEARMOTIV™ 8MS VIDEO RESPONSE



LCD	Type	17" TN colour TFT active matrix SXGA LCD
	Display Area	33.8cm horizontal x 27.0cm vertical, 43.2cm diagonal
	Pixel Pitch	0.264mm
	Optimum Resolution	1280 x 1024@60Hz
	Pixel Clock	135MHz
	Contrast Ratio	600:1 (typ.)
	Viewing Angles	150° horizontal, 135° vertical (at 10:1) 170° horizontal, 155° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 50000 hrs. (min.)
	Brightness	280cd/m ²
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Frequency	F _H : 30-82kHz, F _V : 56-75Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced
	Mac ^{®1}	Power Mac™ up to 1280 x 1024 non-interlaced
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
AUDIO	Speakers	2 x 1.5 watt integrated stereo speakers
POWER	Voltage	AC 100-240V, 50/60Hz (auto switch), internal power supply
	Consumption	35 watt (typ.), <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
CONTROLS	Basic	Power, menu [1], up, down, select [2], mute, volume up/down
	OSD ²	Auto image adjust, contrast, brightness, ViewMatch® colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language [7 options], resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensation)
DIMENSIONS	W x H x D mm	387 x 428 x 206 (with stand) 387 x 367 x 67 (without stand) 445 x 513 x 160 (packaging)
WEIGHT	Net	4.5kg (with stand)
	Gross	5.6kg
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO 13406-2 (pixel failure class II), CB, CE, GOST-R+Hygienic (20 copies), UL, cUL, FCC-B (ICES), ICES-003B, SASO, Energy, ENERGY STAR®, C-Tick, KTL/MIC, BSMI, PSB, TÜV-S, MPR II, VCCI, CCC, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03 and ENERGY standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FDMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers) (multi-language)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK

ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany

Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France

Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation

381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Belux

ViewSonic Denmark

ViewSonic Finland

ViewSonic Italy

ViewSonic MEA

ViewSonic Netherlands

ViewSonic Norway

ViewSonic Spain

ViewSonic Sweden

Tel: +32 (0)56 85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +39 02 73 95 50 22
Tel: +971 (0) 4 88 11 871
Tel: +31 (0)20 491 9254
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VG721m 10/06-UK