

# ViewSonic® PJ1165 Projector

## HIGH BRIGHTNESS MULTIMEDIA SETUP



### High brightness, installed projector for stunning multimedia presentations.

The wide array of features on ViewSonic's PJ1165 projector will impress not only you, but your audience. The PJ1165 projector adds richness and depth to your multimedia presentations with a **REMARKABLE 3,500 LUMENS** and 1024x768 native resolution.

### YOU GET A WIDER RANGE OF INSTALLATION OPTIONS

with the power zoom and focus lens, horizontal and vertical keystone correction. The multiple video and PC inputs, HD signal compatibility, and picture-in-picture function provide maximum versatility. Choose the PJ1165 for large venue installations and conference rooms.



### High-performance, full-featured projector.

...**Bright in virtually any setting with 3,500 lumens**

...**Ultimate flexibility with multiple inputs**

Multiple PC and video inputs provide maximum versatility.

...**Easy set-up and auto tuning**

One-touch setup button for fast, easy sync and sharp focus.

...**Network Control**

Remote management of projector controls and diagnostics.



*Easy-to-use  
remote included.*

...**The perfect image in any setting**

Digital horizontal and vertical keystone correction, power focus and zoom function ensure the perfect size image in any room.

...**Whisper-mode extends lamp life**

Extend the life of your lamp up to 4,000 hours<sup>3</sup> and reduce noise output.

...**Supports HD signals**

Capable of displaying 480i, 480p, 720p and 1080i sources.

...**Progressive scan video**

Reduces flicker and artifacts for clear, stable images.

...**Picture-in-picture capability**

View video and computer data simultaneously for spectacular multimedia presentations.

ViewSonic®



# Super bright

# ViewSonic® PJ1165 Projector

## HIGH BRIGHTNESS MULTIMEDIA SETUP



1. Stand by/on
2. Menu
3. Kensington security port
4. PC/video inputs, outputs and monitor pass through
5. RS-232 and RJ-45
6. Power zoom and focus rings

PJ1165 with Short Throw Lens			
Image Size (Diagonal cm, Wide - Telephoto)	Height (cm, Wide - Telephoto)	Width (cm, Wide - Telephoto)	Throw Distance (cm)
96 - 68	61 - 40	81 - 56	127
152 - 96	91 - 61	122 - 40	150
254 - 172	152 - 104	203 - 137	312
381 - 256	228 - 154	304 - 205	469
508 - 345	304 - 208	406 - 274	375
762 - 505	457 - 312	609 - 406	939
1016 - 670	609 - 401	812 - 535	1249
1270 - 853	762 - 513	1016 - 678	1562

Accuracy of the calculations are +/- 5%.  
For additional calculations visit [ViewSonic.com](http://ViewSonic.com).

### Optional Accessories

- Replacement lamp PRJ-RLC-011
- Wall/ceiling mount PRJ-WMK-011



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.

### MULTIMEDIA PROJECTOR

<b>LCD</b>	Type	0.99" Poly-Si TFT with micro-lens	
	Pixel Format	1024x768 XGA (native resolution)	
	Lens	Power zoom/focus	
	Zoom Factor	1.5	
	Keystone	Vertical ± 15°, horizontal ± 5°	
<b>DISPLAY</b>	Size	1,01m - 14,22m	
	Throw Distance	1,19m - 23,2m	
	Lamp	275W, 4,000 hours <sup>2</sup>	
	Brightness	3,500 lumens	
	Contrast Ratio	800:1	
<b>AUDIO</b>	Speakers	2x1 watts	
	Control Network	RJ-45	
<b>INPUT SIGNAL</b>	Video	RGB analogue, NTSCM, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 575i, 720p, 1080i)	
	Sync	Separated	
	Frequency	F <sub>H</sub> : 15-91KHz; F <sub>V</sub> : 50-120Hz	
<b>COMPATIBILITY</b>	PC	Analogue: from VGA up to UXGA (compressed)	
	Mac <sup>3</sup>	Analogue: up to SXGA	
<b>CONNECTOR</b>	PC (input)	Analogue RGB: DB-15 (x1), Digital RGB: M1-D, BNCx5 connector (x1 set)	
	RGB (output)	DB-15	
	Composite Video (input)	RCA jack (x1)	
	S-Video (input)	Mini-DIN 4-pin (x1)	
	Component Video (input)	RCA jack (x1 set)	
	Audio (input)	3.5mm stereo mini jack (x2) for RGB, RCA L/R jack (x1 set) for video	
	Audio (output)	3.5mm stereo mini jack (x1)	
<b>POWER</b>	Voltage	90-264VAC, 50-60Hz (universal)	
	Consumption	430 watts (typ)	
<b>CONTROLS</b>	Physical	Standby, menu, input, reset, H/V keystone, search, focus, zoom, volume	
	OnView®	Language, display (brightness, contrast, aspect, picture position, gamma, mirror, language, colour bar (R, B) sharpness, colour, tint, V/H position, H phase, H size, over scan, auto adjust, video, HDTV, sync on green, blank, start up, myscreens, myscreens size, myscreens lock, whisper, auto off, audio (volume, mute), projection (front, rear, front ceiling, rear ceiling), lamp (lamp timer, lamp timer reset), filter (filter timer, filter timer reset), service, network	
	Operating Conditions	Temperature: 32-95°F (0-35°C) Humidity: 10-85% (non-condensing)	
	Noise Level	Normal	40dB (typ)
		Whisper Mode	36dB (typ)
	Dimensions	Physical	420mm x 160mm x 320mm (WxHxD)
	Weight	Net	7.7 kg
	Regulations		TÜV/GS, CE, GOST, UL60950/C-UL, FCC B, CB, C-Tick, NOM, CCC, PSB
	Others		Progressive scan, digital gamma correction, over scan, picture-in-picture, remote with mouse control, monitor pass through, auto adjust
	Warranty		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">http://www.viewsoniceurope.com/UK/Support/warranty.htm</a>

# ViewSonic®



**ViewSonic Europe Limited/UK**  
ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbanniers  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +32 056/85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (9) 54 06 40 70  
Tel: +39 02 5832 0356  
Tel: +971 (0) 4 88 11 871  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> The warranty for all ViewSonic LCD and DLP projectors (except PJ250) from 1 April 2004 is valid for three years, and includes an on-site exchange service during this period in the most European Union (France, Belgium, Netherlands, Luxembourg, United Kingdom, Ireland, Sweden, Denmark, Finland, Germany, Austria, Greece, Italy, Spain, Portugal) and EFTA countries (Switzerland, Liechtenstein, Norway, Iceland).  
<sup>2</sup> Running whisper-mode exclusively can extend lamp life up to 4,000 hours. <sup>3</sup> Optional cables required. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2004 ViewSonic Corporation. All rights reserved. PJ1165 08/04-UK

For more product information, visit us on the web at [ViewSonicEurope.com](http://ViewSonicEurope.com)